

## Spectrum Routeline CR Paint White



### SAFETY DATA SHEET

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) 453/2010

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

**Product Name** Spectrum Routeline CR Paint White  
**Product Inclusion** This document covers Spectrum Routeline CR Paint White only.

##### 1.2. Relevant identified uses of the substance of mixture and uses advised against

**Identified Uses** See technical data sheet. For professional use only.  
**Uses advised against** No specific uses advised against are identified.

##### 1.3. Details of the supplier of the safety data sheet

**Supplier** Meon Ltd.  
Railside  
Northharbour Spur  
Portsmouth  
PO6 3TU  
+44 (0) 23 9220 0606  
+44 (0) 23 9220 0707  
mail@meonuk.com

##### 1.4. Emergency Telephone Number

**Emergency telephone** +44 (0) 808 118 1922

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

Classification according to Classification, Labeling & Packaging Regulation (EC) 1272/2008

Flam. Liq. 2 - H225, Skin Irrit. 2 - H315, STOT SE. 3 - H336, Rep. Tox. 2 - H361d and STOT RE. 2 - H373.

##### Environmental hazards

Not classified

##### 2.2. Label Elements

Hazard pictograms



**Signal word** Danger  
**Named Chemicals on Label**  
**Contains**  
**H-statement(s)** H225 Highly flammable liquid and vapour.

## Spectrum Routeline CR Paint White

H315 Causes skin irritation.  
 H361d Suspected of damaging the unborn child.  
 H373 May cause damage to organs through prolonged or repeated exposure.

**P-statement(s)**  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P260 Do not breath dust, fume, gas, mist, vapours or spray.  
 P280 Wear protective gloves, protective clothing, eye protection and face protection.  
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P308+P313 IF exposed or concerned: Get medical advice or attention.  
 P403+P235 Store in a well-ventilated place. Keep cool.

**Supplemental hazard information** EUH 208 Contains 2-butanone oxime. May produce an allergic reaction.

### 2.3. Other hazards

#### Results of PBT and vPvB assessment:

PBT and vPvB not applicable.

### SECTION 3: Composition/information on ingredients

SUBSTANCE [ ] MIXTURE [X]

#### Description of mixture

Mixture of resins, solvents, pigments and additives.

#### Dangerous component(s)

Ingredient	Cas-No: EC No: Reach No:	R-Phrases	Concentration
		CLP Hazard Statements	
Toluene	108-88-3 203-625-9 -		10.0-25.0%
		H225, H304, H315, H336, H361d, H373	
Xylene	1330-20-7 215-535-7 -		2.5-10.0%
		H226, H312, H315, H332	
Ethylbenzene	100-41-4 202-849-4 -		<0.6%
		H225, H332	
2-butanone oxime	96-29-7 202-496-6 01-2119539477-28		0.1-1.0%
		H311, H317, H318, H351	

**Additional Information:** The text for CLP Hazard Statements shown above (if any) is given in Section 16.

### SECTION 4: First aid measures

Show this safety data sheet to the doctor in attendance.

#### 4.1. Description of first aid measures

**General notes** In case of doubt, or symptom persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

**In case of inhalation:** Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

**In case of skin contact:** Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

**In case of eye contact:** Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

## Spectrum Routeline CR Paint White

**In case of ingestion:** If accidentally swallowed rinse mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

**Self-protection of the first aider:** None.

### **4.2. Most important symptoms and effects, both acute and delayed**

None

### **4.3. Indication of any immediate medical attention and special treatment needed**

**Notes to Physician:** None.

**Specific treatment:** None.

---

## **SECTION 5: Firefighting measures**

### **5.1. Extinguishing media**

**Suitable extinguishing media** Alcohol-resistant foam, CO<sub>2</sub>, powders, water spray/mist.

**Extinguishing media which must not be used for safety reasons** Water jet.

### **5.2. Special hazards arising from the substance or mixture**

**Specific hazard** Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required.

### **5.3. Advice for firefighters**

**Protective actions during firefighting.** Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or watercourses.

---

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Exclude sources of ignition and ventilate the area. Avoid breathing vapours.

### **6.2. Environmental precautions**

Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

### **6.3. Methods and material for containment and cleaning up**

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations. Clean preferably with a detergent – avoid use of solvents.

### **6.4. Reference to other sections**

None.

---

## **SECTION 7: Handling and storage**

### **7.1. Precautions on safe handling**

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been included. Electrical equipment should be protected to the appropriate standard.

Mixture may charge electrostatically: always use earthing leads when transferring from one container to another.

Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Isolate from sources of heat, sparks and open flame, no sparking tools should be used, avoid skin and eye contact, avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture and avoid inhalation of dust from sanding.

Smoking, eating and drinking should be prohibited in application area, for personal protection see Section 8, never use pressure to empty: container is not a pressure vessel, always keep in containers of same material as the original one, comply with the health and safety at work laws and do not allow to enter drains or watercourses.

### **Advice on protection against fire and explosion**

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

## Spectrum Routeline CR Paint White

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage areas and containers

Store in accordance with the Dangerous Substances and Explosive Atmospheres Regulations, 2002, (DSEAR). The requirements are given in the HSE Approved Code of Practice and Guidance, Storage of Dangerous Substances: DSEAR.

#### Notes on joint storage

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

#### Additional information on storage conditions

Observe label precautions. Store between 5 °C and 25°C in a dry well ventilated place away from sources of heat and direct sunlight. Keep container tightly closed. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers which are opened must be carefully resealed and kept upright to prevent leakage. The principles contained in the HSE guidance note, Chemical Warehousing: The Storage of Packaged Dangerous Substances, should be observed when storing this product.

### 7.3. Specific end uses

No specific advice for end use available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Ingredients with Occupational Exposure Limits (UK WELS)

Name	LTEL ppm	STEL ppm	STEL mg/m <sup>3</sup>	LTEL mg/m <sup>3</sup>	Notes
Toluene	50	100	384	191	Sk,
Xylene	50	100	441	220	Sk, BMGV
Ethylbenzene	100	125	552	441	Sk

### 8.2. Exposure controls

#### Engineering measures

Provide adequate ventilation. Suitable respiratory protection must be worn if local exhaust ventilation and good general extraction are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL.

#### Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators.

#### Eye/face protection

Use safety eyewear designed to protect against splash of liquids.

#### Hand protection

For prolonged or repeated handling, use Polyvinyl Alcohol (PVA) OR Viton Rubber (FluorRuber). Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

#### Other skin and body protection

Personnel should wear anti-static clothing made of natural fibre or high temperature resistant synthetic fibre.

#### Environmental exposure controls

Do not allow to enter drains or watercourses.

## SECTION 9: Physical and Chemical Properties

### 9.1. Information on basic physical and chemical properties

Appearance:	Viscous liquid
Colour:	Various
Odour:	Aromatic hydrocarbon.
Melting point/freezing point:	>-95°C
Initial boiling point and boiling range	110-140
Flash point:	4°C
Vapour pressure:	>0.3 kPa 20.0
Vapour density(air=1):	>1.0
Relative density(g/ml):	1.39-1.55
Solubility:	Miscible with organic solvents.
Partition coefficient:	2.65 log Pow
Auto ignition temperature:	>480°C

## Spectrum Routeline CR Paint White

**Viscosity:** 2.0 poise.  
**Explosive properties:** May form explosives mixture with air.

### **9.2. Other information**

None.

### **SECTION 10: Stability and reactivity**

#### **10.1. Reactivity**

No data available.

#### **10.2. Chemical stability**

Stable under recommended storage and handling conditions.

#### **10.3. Possibility of hazardous reactions**

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

#### **10.4. Conditions to avoid**

When exposed to high temperatures may produce hazardous decomposition products.

#### **10.5. Incompatible materials**

No data available.

#### **10.6. Hazardous decomposition products**

Carbon monoxide and dioxide, smoke, oxides of nitrogen.

### **SECTION 11: Toxicological information**

No data available.

The mixture has been assessed following the conventional method of the Classification, Labelling and Packaging of Substances and Mixtures Regulation (EC) No. 1272/2008, (CLP) and classified for toxicological hazards accordingly.

#### **11.1. Information on toxicological effects**

<b>Repeated and prolonged contact with mixture</b>	Cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.
<b>Liquid splashed into eyes:</b>	Cause irritation and reversible damage.
<b>Ingestion:</b>	May cause nausea, diarrhoea and vomiting.
<b>Exposure to component solvent: vapour concentration in excess of stated occupational limit</b>	May result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.
<b>Symptoms and signs:</b>	Include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

#### **Additional information**

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

### **SECTION 12: Ecological information**

#### **12.1. Toxicity**

No information.

#### **12.2. Persistence and degradability**

No information.

#### **12.3. Bioaccumulative potential**

Not available.

#### **12.4. Mobility in soil**

No information.

#### **12.5. Results of PBT and vPvB assessment**

Not available.

#### **12.6. Other adverse effects**

No information.

### **SECTION 13: Disposal considerations**

#### **13.1. Waste treatment methods**

Do not allow to enter drains or watercourses.

Residues in empty containers should be neutralised with decontaminant.

#### **European List of Waste classification**

Waste code: Name of Waste (according to Commission Decision 2000/532/EC):

## Spectrum Routeline CR Paint White

08 01 11\* Waste paint and varnish containing organic solvents or other dangerous substances.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information contact your local waste authority. Using information provided in this safety data sheet, advice should be obtained from the local waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

### SECTION 14: Transport information



<b>14.1 UN number:</b>	1263
<b>14.2 UN proper shipping name</b>	PAINT
<b>14.3 Transport hazard class(es)</b>	3
<b>14.4 Packing group</b>	II
<b>14.5 Environmental hazards</b>	None.
<b>14.6 Special precautions for user</b>	Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
ADR Tunnel Restriction Code	(D/E)
IMDG EmS	F-E, S-E
IMDG Stowage Category	B
<b>14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code</b>	Not available

### SECTION 15: Regulatory information

#### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**The information in this Safety Data Sheet is required pursuant to:**

Registration, Evaluation, Authorisation and Restriction of Chemicals, Regulation (EC) No. 1907/2006, (REACH).

Classification, Labelling and Packaging of substances and mixtures, Regulation (EC) No. 1272/2008, (CLP).

The Dangerous Substances and Explosive Atmosphere Regulations, 2002, (DSEAR).

The Control of Substances Hazardous to Health Regulations, 2002, (COSHH).

The Health and Safety at work etc Act, 1974, (HSWA)

**Approved codes of Practice and Guidance notes relevant to this Safety Data Sheet:**

The European Chemicals Agency (ECHA) Guidance on the compilation of safety data sheets, Version 2.1.

CEPE Guideline for Safety Data Sheets, 9th Edition.

HSE Approved Code of Practice and Guidance, Dangerous Substances and Explosive Atmospheres.

HSE guidance note, Chemical Warehousing: The Storage of Packaged Dangerous Substances.

HSE publication, EH40/2005 Workplace exposure limits.

## Spectrum Routeline CR Paint White

### 15.2 Chemical safety assessment

No chemical safety assessment has been carried out for this mixture by the supplier.

### **SECTION 16: Other information**

#### **Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**

H225 : Highly flammable liquid and vapour.

H226 : Flammable liquid and vapour.

H304 : May be fatal if swallowed and enters airways.

H311 : Toxic in contact with skin.

H312 : Harmful in contact with skin.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.

H318 : Causes serious eye damage.

H332 : Harmful if inhaled.

H336 : May cause drowsiness or dizziness.

H351 : Suspected of causing cancer.

H361d : Suspected of damaging the unborn child.

H373 : May cause damage to organs through prolonged or repeated exposure.

#### **List of Wastes"Acronym & Abbreviation Key:**

BMGV Biological Monitoring Guidance Values are given in Table 2 of EH40/2005 Workplace exposure limits.

Sk Can be absorbed through the skin. Dermal absorption may lead to systemic toxicity.

CLP Classification, Labelling & Packaging Regulation

EC European Commission

EU European Union

US United States

CAS Chemical Abstract Service

EINECS European Inventory of Existing Chemical Substances

REACH Registration, Evaluation, Authorization of Chemicals Regulation

GHS Globally Harmonized System of Classification and Labeling of Chemicals

LTEL Long term exposure limit

STEL Short term exposure limit

OEL Occupational exposure limit

ppm Parts per million

mg/m<sup>3</sup> Milligrams per cubic meter

TLV Threshold Limit Value

ACGIH American Conference of Governmental Industrial Hygienists

OSHA Occupational Safety & Health Administration

PEL Permissible Exposure Limits

VOC Volatile organic compounds

g/l Grams per liter

mg/kg Milligrams per kilogram

N/A Not applicable

LD50 Lethal dose at 50%

LC50 Lethal concentration at 50%

EC50 Half maximal effective concentration

IC50 Half maximal inhibitory concentration

PBT Persistent bioaccumulative toxic chemical

vPvB Very persistent and very bioaccumulative

EEC European Economic Community

ADR International Transport of Dangerous Goods by Road

RID International Transport of Dangerous Goods by Rail

UN United Nations

IMDG International Maritime Dangerous Goods Code

IATA International Air Transport Association

MARPOL International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978

IBC International Bulk Container

## Spectrum Routeline CR Paint White

This information is provided in accordance with the current status of our knowledge and experience. The Safety Data Sheet describes products with a view to relevant safety requirements. This information does not constitute a warranty of properties, features or qualities.